


SMOOTH FILM PLYWOOD

Suitable for formwork systems, scaffolding, transport industry, construction works.



WIRE MESH PLYWOOD

Suitable for platforms, stage systems, vehicle and trailer floors.

FILM SPECIFICATIONS

- Dark brown phenolic film
- Edges sealed with water resistant paint
- Film density 120 g/m²; 220 g/m²

PRODUCTION STANDARD

- EN 636-3S

CERTIFICATION

- FSC Mix Credit
- CE
- UKCA
- CARB Phase 2/TSCA
- EN 717-1

GLUE CONTENTS

- Phenol Formaldehyde (WBP), E1

VENEER THICKNESS

- 1,5 mm

SIZES

- 1250x2500
- 1220x2440

MOISTURE CONTENT

- 10% +/- 2%

ALL OUR
PLYWOOD
IS PRODUCED
WITH
100% BIRCH

THICKNESS TOLERANCE FOR SANDED MATERIAL (Special thickness tolerances available upon request)

Nominal Thickness	6,5	9	12	15	18	21	24	27	30	35	40
Number of plies	5	7	9	11	13	15	17	19	21	25	29
Minimum	6,1	8,8	11,5	14,3	17,1	20,0	22,9	25,2	28,1	33,5	38,8
Maximum	6,9	9,5	12,5	15,3	18,7	21,5	24,5	26,8	30,5	35,5	41,2

PLYWOOD PACKAGING

Thickness	6,5	9	12	15	18	21	24	27	30	35	40
Number of sheets per pack	110	80	60	50	40	35	30	27	25	21	18
m ³ per pack 1250x2500	2,234	2,25	2,25	2,344	2,25	2,297	2,25	2,278	2,344	2,296	2,25
m ³ per pack 1220x2440	2,128	2,143	2,143	2,233	2,143	2,188	2,143	2,170	2,232	2,187	2,143
m ² per pack 1250x2500	343,75	250	187,5	156,25	125	109	93,75	84,38	78,13	65,62	56,25
m ³ per pack 1220x2440	327,47	238,16	178,62	148,85	119,08	104,20	89,31	80,38	74,43	62,52	53,59

