



C GRADE

Suitable for use where surface appearance is not important, as packaging material.



CP GRADE

Suitable for construction works, production of packaging materials, further veneering.



BB GRADE

Suitable for interior and exterior finishing, painting or decoration, furniture, sports equipment, etc.



S GRADE

Suitable for interior, furniture production, laquering.

GRAIN DIRECTION

- Cross grain only

PRODUCTION STANDARD

- EN 636-2S

CERTIFICATION

- FSC Mix Credit
- PEFC
- F4
- CE
- UKCA
- CARB Phase 2/TSCA
- EN 717-1

GLUE CONTENTS

- Phenol Formaldehyde (WBP), E1

VENEER THICKNESS

- 1,5 mm

SIZES

- 1250x2500
- 1220x2440

MOISTURE CONTENT

- 10% +/- 2%

ALL OUR
PLYWOOD
IS PRODUCED
WITH
100% BIRCH

THICKNESS TOLERANCE FOR SANDED MATERIAL (Special thickness tolerances available upon request)

| Nominal Thickness | 6,5 | 9 | 12 | 15 | 18 | 21 | 24 | 27 | 30 | 35 | 40 |
|-------------------|-----|-----|------|------|------|------|------|------|------|------|------|
| Number of plies | 5 | 7 | 9 | 11 | 13 | 15 | 17 | 19 | 21 | 25 | 29 |
| Minimum | 6,1 | 8,8 | 11,5 | 14,3 | 17,1 | 20,0 | 22,9 | 25,2 | 28,1 | 33,5 | 38,8 |
| Maximum | 6,9 | 9,5 | 12,5 | 15,3 | 18,7 | 21,5 | 24,5 | 26,8 | 30,5 | 35,5 | 41,2 |

PLYWOOD PACKAGING

| Thickness | 6,5 | 9 | 12 | 15 | 18 | 21 | 24 | 27 | 30 | 35 | 40 |
|-----------------------------------|--------|--------|--------|--------|--------|--------|-------|-------|-------|-------|-------|
| Number of sheets per pack | 110 | 80 | 60 | 50 | 40 | 35 | 30 | 27 | 25 | 21 | 18 |
| m ³ per pack 1250x2500 | 2,234 | 2,25 | 2,25 | 2,344 | 2,25 | 2,297 | 2,25 | 2,278 | 2,344 | 2,296 | 2,25 |
| m ³ per pack 1220x2440 | 2,128 | 2,143 | 2,143 | 2,233 | 2,143 | 2,188 | 2,143 | 2,170 | 2,232 | 2,187 | 2,143 |
| m ² per pack 1250x2500 | 343,75 | 250 | 187,5 | 156,25 | 125 | 109 | 93,75 | 84,38 | 78,13 | 65,62 | 56,25 |
| m ² per pack 1220x2440 | 327,47 | 238,16 | 178,62 | 148,85 | 119,08 | 104,20 | 89,31 | 80,38 | 74,43 | 62,52 | 53,59 |