



C GRADE

Suitable for use where surface appearance is not important, as packaging material.



CP GRADE

Suitable for construction works, production of packaging materials, further veneering.



BB GRADE

Suitable for interior and exterior finishing, painting or decoration, furniture, sports equipment, etc.



S GRADE

Suitable for interior, furniture production, laquering.

GRAIN DIRECTION

- Cross grain only

PRODUCTION STANDARD

- EN 636-2S

CERTIFICATION

- FSC Mix Credit
- PEFC
- F4
- CE
- UKCA
- CARB Phase 2/TSCA
- EN 717-1

GLUE CONTENTS

- Phenol Formaldehyde (WBP), E1

VENEER THICKNESS

- 1,5 mm

SIZES

- 1250x2500
- 1220x2440

MOISTURE CONTENT

- 10% +/- 2%

ALL OUR
PLYWOOD
IS PRODUCED
WITH
100% BIRCH

THICKNESS TOLERANCE FOR SANDED MATERIAL (Special thickness tolerances available upon request)

Nominal Thickness	6,5	9	12	15	18	21	24	27	30	35	40
Number of plies	5	7	9	11	13	15	17	19	21	25	29
Minimum	6,1	8,8	11,5	14,3	17,1	20,0	22,9	25,2	28,1	33,5	38,8
Maximum	6,9	9,5	12,5	15,3	18,7	21,5	24,5	26,8	30,5	35,5	41,2

PLYWOOD PACKAGING

Thickness	6,5	9	12	15	18	21	24	27	30	35	40
Number of sheets per pack	110	80	60	50	40	35	30	27	25	21	18
m ³ per pack 1250x2500	2,234	2,25	2,25	2,344	2,25	2,297	2,25	2,278	2,344	2,296	2,25
m ³ per pack 1220x2440	2,128	2,143	2,143	2,233	2,143	2,188	2,143	2,170	2,232	2,187	2,143
m ² per pack 1250x2500	343,75	250	187,5	156,25	125	109	93,75	84,38	78,13	65,62	56,25
m ² per pack 1220x2440	327,47	238,16	178,62	148,85	119,08	104,20	89,31	80,38	74,43	62,52	53,59

