

Certificate of constancy of performance No. 1325-CPR-4243A

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product(s)

Wood wool (WW) thermal insulation products
Boards
Sonablock Fiber and Sonablock Firesafe Fiber
according to the Annex,

PLACED ON THE MARKET UNDER THE NAME OF:

SIA „Stiga RM”

Meistaru iela 1, Kuldīga, Kuldīgas nov., LV-3301, Latvia; Reg. Nr. 40003194846

PLANT ADDRESS:

SIA „Stiga RM” plant “Loka ceļš septiņi A”, Smārdes pagasts, Tukuma novads, LV-3129, Latvia

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 13168:2012+A1:2015

Under system 1 for the performance set out in this certificate are applied and that **the performance of the construction product is assessed to remain constant.**

This certificate was first issued on 16 March 2026 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by notified factory production control certification body.

27 July 2026

Mārtiņš Maskavs
Certification Manager



Certificate issued on 1 (one) page with Annex on 1 (one) page



EN ISO/IEC 17065
S1-182

AS Kiwa Latvia
Skanstes iela 54, Rīga
LV-1013, Latvija

T. +371 67 607 900
latvia@kiwa.com

www.kiwa.com/lv

Product: Wood wool (WW) thermal insulation products: boards *Sonablock Fiber* and *Sonablock Firesafe Fiber*.

Manufacturer: SIA „Stiga RM” ražotne “Loka ceļš septiņi A”, Smārdes pagasts, Tukuma novads, LV-3129, Latvia.

Sonablock Fiber	
Thickness of board	25 mm
Wood shavings	1 mm / 1,5 mm
Binder	Cement, sodium silicate, limestone dust
Density of board	
With wood shavings of 1 mm	410 kg/m ³ (±15%)
With wood shavings of 1,5 mm	470 kg/m ³ (±15%)
Paint (if used) - MasqueTop W 830	
Red, black	400 g/m ²
White	260 g/m ²
Reaction to Fire	B-s1,d0
Sonablock Firesafe Fiber	
Thickness of board	25 mm
Wood shavings	1 mm / 1,5 mm
Binder	Cement, sodium silicate, limestone dust
Density of board	
With wood shavings of 1 mm	678 kg/m ³ (±15%)
With wood shavings of 1,5 mm	718 kg/m ³ (±15%)
Paint (if used) - MasqueTop W 830	
Red, black	400 g/m ²
White	260 g/m ²
Reaction to Fire	A2-s1,d0

27 July 2026

Mārtiņš Maskavs

Certification Manager



EN ISO/IEC 17065
S1-182

AS Kiwa Latvia
Skanstes iela 54, Rīga
LV-1013, Latvija

T. +371 67 607 900
latvia@kiwa.com

www.kiwa.com/lv